




**Séparateurs Eau/huile**

Modèle	Entrée condensats mm	Dimensions (mm)					Poids KG	Prix (Euro)	Options (Euro)	
		A	B	C	D	E			kit de maintenance	Kit résistance électrique
SAO 16	10	300	464	525	200	/	4	450	140	/
SAO 33	13	345	685	755	360	445	10	930	140	640
SAO 100	25	480	900	1 000	540	665	24	1 740	260	1 140
SAO 190	25	630	1 050	1 150	590	680	30	1 970	320	1 140
SAO 340	25	590	1 145	1 245	670	920	40	2 550	550	1 510
SAO 1020	25	905	1 515	1 615	1 000	1 200	90	8 750	1 330	2 060

Notes :

- Emballage avec nylon + carton pour les modèles.

		SAO performance according to air compressor type											
		Oil injected rotary screw and vane compressors								1 or 2 stage recipr. compressors			
		turbine oil		VDL-oil		VCL-oil		synthetic oil		turbine oil		VDL or synthetic oil	
climatic area	model	m <sup>3</sup> /h	m <sup>3</sup> /min	m <sup>3</sup> /h	m <sup>3</sup> /min	m <sup>3</sup> /h	m <sup>3</sup> /min	m <sup>3</sup> /h	m <sup>3</sup> /min	m <sup>3</sup> /h	m <sup>3</sup> /min	m <sup>3</sup> /h	m <sup>3</sup> /min
	SAO 16	90	1,5	78	1,3	60	1,0	18-60	0,3-1	60	1	24-42	0,4-0,7
	SAO 33	240	4	210	3,5	150	2,5	72-150	1,2-2,5	120	2	42-84	0,7-1,4
	SAO 100	510	8,5	42	7	330	5,5	138-330	2,3-5,5	264	4,4	84-198	1,4-3,3
	SAO 190	990	16,5	870	14,5	660	11,0	330-660	5,5-11	528	8,8	198-390	3,3-6,5
	SAO 340	1980	33	1800	30	1320	22,0	660-1320	11-22	1320	22	390-408	6,5-6,8
	SAO 1020	6300	105	5400	90	4200	70,0	1500-4200	25-70	4200	70	1020-3120	17-52
	SAO 16	150	2,5	120	2	90	1,5	30-90	0,5-1,5	72	1,2	30-54	0,5-0,9
	SAO 33	270	4,5	240	4	180	3	84-180	1,4-3	144	2,4	54-96	0,9-1,6
	SAO 100	600	10	540	9	420	7	150-420	2,5-7	336	5,6	150-270	2,5-4,6
	SAO 190	1260	21	1080	18	840	14	360-840	6-14	672	11,2	300-630	5-10,5
	SAO 340	2700	45	2400	40	1800	30	840-1800	14,0-30	1440	24	600-1200	10-20
	SAO 1020	7200	120	6000	100	4800	80	2100-4800	35-80	4800	80	2100-4500	35-75
	SAO 16	60	1	42	0,7	30	0,5	12-30	0,2-0,5	24	0,4	12-24	0,2-0,4
	SAO 33	150	2,5	120	2	90	1,5	60-90	1-1,5	60	1	30-60	0,5-1
	SAO 100	330	5,5	270	4,5	210	3,5	120-210	2-3,5	168	2,8	84-168	1,4-2,8
	SAO 190	630	10,5	540	9	420	7	270-420	4,5-7	336	5,6	150-336	2,5-5,6
	SAO 340	1380	23	1200	20	900	15	600-900	10-15	720	12	300-720	5-12
	SAO 1020	3600	60	3000	50	2400	40	1320-2400	22-40	2400	40	900-2100	15-35

